



BRASS SERVICE CONDUIT MARKER

LEGEND

- * NOM kerb line
- ⊗ Service conduit marker
- Refer project drawings.
- Service conduit to be offset 0.8 metre on low side from subdivisinal boundary.
- SC — Service conduits (on project drawings).

NOTES:

1. Trimming and compaction of the subgrade to be completed and approved before excavation for service conduits is commenced. Excavated material shall be thrown on the footpath and not on the subgrade.
2. Service conduits alternatives :- 100 DIA concrete/FR pipes (S.F.) Class C or S (R.R.J.)
100 DIA uPVC, Class 12.
3. Positions of the service conduits shown are typical only. Conduits to be located as shown on project drawings.
4. Where concrete footpaths/cyclepaths exist or are planned, the service conduit is to extend past the far side of the path.
5. Marker details may be varied if approved.
6. All dimensions in millimetres.

B	Dimension to end of conduit and text size on marker	16/1/97
A	ORIGINAL ISSUE	8/12/95
REVISIONS		DATE

© INSTITUTE OF MUNICIPAL ENGINEERING AUSTRALIA QUEENSLAND DIVISION INC. - 1995
 DISCLAIMER. The authors and sponsoring organisations shall have no liability or responsibility to the user or any other person or entity with respect to any liability, loss or damage caused or alleged to be caused, directly or indirectly, by the adoption and use of these Standard Drawings including, but not limited to, any interruption of service, loss of business or anticipatory profits, or consequential damages resulting from the use of these Standard Drawings. Persons must not rely on these Standard Drawings as the equivalent of, or a substitute for, project-specific design and assessment by an appropriately qualified professional.



WATER SERVICE CONDUITS

ROAD/STREET	
Standard Drawing	
R-0160	
A	B